Welcome! to our world



## net started

## RM 70GO! 2.0 THE CRUSHER FOR NEWCOMERS MAXIMUM MOBILITY, EASY OPERATION.



2.0



Welcome! to our world

## daton

## **RM 70GO! 2.0 – TRACKED MOBILE IMPACT CRUSHER**

Output	Up to 150 t/h, depending on material
Feed material size	Edge length max. 600 mm
Inlet opening	760 x 600 mm
Crusher unit	RUBBLE MASTER impact crusher with 2 or 4 hammers, 1 rotor speed
Operation	One operator using radio control for crushing and manoeuvring operations
Feed unit	Asymmetric vibro feeder with 2 m³ and 2 unbalanced motors each 3.1 kW, loading height 2,660 mm, effective feed length and width: 2,500 x 1,800 mm
	feed control system for automatic crusher feeding Hardox 400 wear lining
Prescreening	Efficient prescreen with mesh screen
	screen area 1,000 x 700 mm discharge on main conveyor belt by means of fully integrated bypass chute
Main discharge belt (crushed material)	Folding conveyor 800 mm wide, folds into transport position hydraulically Discharge height 2,720 mm
Power Unit	John Deere (Stage III A at constant engine speed), 4-Zylinder, 115 kW at 1.800 Upm certified, synchronous generator 40 kVA 400 V, electrical outlets 230 V and 400 V for external drives up to 15 kVA
Release system	To remove blockages inside crusher
Magnetic separator	Ultra-strong magnet, operates to left and right, belt width 800 mm
Transport system	Crawler gear
Weight	19.500 kg
Options	Dust suppression using water spray inside crusher and at outlet and belts
	Diesel filling pump
	Diesel filling pump Crusher hammer changing system
	Crusher hammer changing system
	Crusher hammer changing system Cable remote control